

Overview

HP U200 Unified Threat Management (UTM) Appliance Series (Retired)

Models

HP U200-S UTM Appliance

JD273A

HP U200-A UTM Appliance

JD275A

Key features

- Flexible security zone and virtual firewall
- Advanced VPN
- Comprehensive threat protection
- Antivirus, antispam, and URL filtering options
- Intelligent Web-based management

Product overview

The HP U200 Unified Threat Management (UTM) Appliance Series comprises a group of purpose-built security devices designed to provide comprehensive protection for distributed environments such as branch offices and remote sites. Utilizing a state-of-the-art multicore platform and advanced hardware acceleration, the U200 UTM appliance series delivers robust protection against malicious attacks that could compromise networks and their critical assets. Sharing the same proven technology as the HP VPN Firewall Module Family, the U200 UTM appliance series provides protection against known threats such as malware and denial-of-service (DoS) attacks while providing optional services such as antivirus, antispam, and URL filtering capabilities. This provides manageable, flexible security options for organizations and their unique deployment needs.

Features and benefits

Application highlights

- **Enhanced firewall functions:** provide basic functions such as security zone configuration, static/dynamic blacklist, MAC-IP binding, and ACL application; offer enhanced functions like status-based filtering, virtual firewall, and transportation of IEEE 802.1Q-tagged packets; protect the network against attacks from ARP spoofing, invalid TCP flag, large ICMP packets, Challenge Collapsar (CC), SYN flooding, and address/port scanning
- **Abundant VPN features:** HP U200 UTM appliances support access through L2TP VPN, GRE VPN, and IPSec VPN and SSL VPN; the integrated hardware encryption engine implements VPN handling of high performance
- **Zone-based access policies:** logically groups virtual LANs (VLANs) into zones that share common security policies; allows both unicast and multicast policy settings by zones instead of by individual VLANs
- **Application-level gateway (ALG):** deep packet inspection in the firewall discovers the IP address and service port information embedded in the application data; the firewall then dynamically opens appropriate connections for specific applications
- **Full support of NAT applications:** HP U200 UTM appliances support NAT applications, including many-to-one, many-to-many, static NAT, dual translation, easy IP, and DNS mapping; support NAT traversal with multiple protocols, and deliver NAT ALG functions such as DNS, FTP, H.323, and NBT
- **Real-time antivirus:** HP U200 UTM appliances adopt Kaspersky's antivirus engine to detect and remove codes of malicious attacks in a timely manner
- **Real-time spam filtering:** HP U200 UTM appliances filter spam in real time, which purifies mail systems
- **URL filtering:** HP U200 UTM appliances implement user-based URL access control to deny access to unauthorized websites
- **Enterprise-class high availability:** dual-box failover protects against loss of connectivity due to hardware failure, with automatic configuration and state table synchronization to simplify administration and remove scope for security policy inconsistencies

Management

- **Complete session logging:** provides detailed information for problem identification and resolution

Overview

- **Manager and operator privilege levels:** enable read-only (operator) and read/write (manager) access on CLI and Web browser management interfaces
- **Secure Web GUI:** provides a secure, easy-to-use graphical interface for configuring the module via HTTPS
- **Command-line interface (CLI):** provides a secure, easy-to-use command-line interface for configuring the module via SSH or a switch console; provides direct real-time session visibility
- **SNMPv1, v2c, and v3:** facilitate centralized discovery, monitoring, and secure management of networking devices
- **Remote monitoring (RMON):** uses standard SNMP to monitor essential network functions; supports events, alarm, history, and statistics group plus a private alarm extension group
- **FTP, TFTP, and SFTP support:** FTP allows bidirectional transfers over a TCP/IP network and is used for configuration updates; Trivial FTP is a simpler method using User Datagram Protocol (UDP)

Warranty and support

- **1-year warranty:** with advance replacement and 30-calendar-day delivery (available in most countries)
- **Electronic and telephone support:** limited electronic and telephone support is available from HP; to reach our support centers, refer to <http://www.hp.com/networking/contact-support>; for details on the duration of support provided with your product purchase, refer to <http://www.hp.com/networking/warrantysummary>
- **Software releases:** to find software for your product, refer to <http://www.hp.com/networking/support>; for details on the software releases available with your product purchase, refer to <http://www.hp.com/networking/warrantysummary>

Technical Specifications

HP U200-S UTM Appliance (JD273A)

Ports	1 RJ-45 serial console port 5 auto-negotiating 10/100/1000 ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T) 1 Compact Flash port 1 module slot	
Physical characteristics	Dimensions	11.81(w) x 10.59(d) x 1.72(h) in (30 x 26.9 x 4.36 cm) (1U height)
	Weight	5.51 lb (2.5 kg)
Memory and processor	512 MB DDR2 SDRAM	
Performance	MAC address table size	4000 entries
Environment	Operating temperature	32°F to 113°F (0°C to 45°C)
	Operating relative humidity	10% to 95%, noncondensing
Electrical characteristics	Voltage	100-240 VAC
	Current	1.5 A
	Maximum power rating	54 W
	Frequency	50 / 60 Hz
	Notes	Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.
Safety	IEC 60950-1, Second Edition; UL60950-1, First Edition; EN60950-1, First Edition	
Emissions	VCCI Class B; EN 55022 Class B; ICES-003 Class B; FCC Part 15, Class B; EN 61000-3-2; EN 61000-3-3	
Management	IMC - Intelligent Management Center; command-line interface; Web browser; SNMP Manager; Telnet; HTTPS; FTP; Support HP A-IMC UTM Manager Software as unified management platform	
Notes	Performance	
	• 200 Mbps firewall throughput	
	• 60,000 concurrent connections under firewall mode/16,000 concurrent connections under UTM mode	
	• 6,000 new connections per second under firewall mode/2,000 new connections per second under UTM mode	
	• 1,000 security policies	
	• 100 Mbps 3DES/AES VPN throughput	
	• 100 IPSec tunnels	
	• 30 Mbps antivirus throughput	
Services	Refer to the HP website at: http://www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.	

HP U200-A UTM Appliance (JD275A)

Ports	RJ-45 serial console port 6 auto-negotiating 10/100/1000 ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T) 1 Compact Flash port 2 module slots	
Physical characteristics	Dimensions	17.4(w) x 16.06(d) x 1.74(h) in (44.2 x 40.8 x 4.42 cm) (1U height)
	Weight	8.82 lb (4 kg)
Memory and processor	1 GB DDR2 SDRAM	

Technical Specifications

Performance	MAC address table size	4000 entries
Environment	Operating temperature	32°F to 113°F (0°C to 45°C)
	Operating relative humidity	10% to 95%, noncondensing
Electrical characteristics	Voltage	100-240 VAC
	Current	2.5 A
	Maximum power rating	100 W
	Frequency	50 / 60 Hz
	Notes	Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.
Safety	IEC 60950-1, Second Edition; UL60950-1, First Edition; EN60950-1, First Edition	
Emissions	VCCI Class B; EN 55022 Class B; ICES-003 Class B; FCC Part 15, Class B; EN 61000-3-2; EN 61000-3-3	
Management	IMC - Intelligent Management Center; command-line interface; Web browser; SNMP Manager; Telnet; HTTPS; FTP; Support HP A-IMC UTM Manager Software as unified management platform	
Notes	Performance	
	• 800 Mbps firewall throughput	
	• 500,000 concurrent connections under firewall mode/100,000 concurrent connections under UTM mode	
	• 10,000 new connections per second under firewall mode/5,000 new connections per second under UTM mode	
	• 10,000 security policies	
	• 400 Mbps 3DES/AES VPN throughput	
	• 1000 IPsec tunnels	
• 100 Mbps antivirus throughput		
Services	Refer to the HP website at http://www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.	

Standards and protocols (applies to all products in series)	IPv6
	RFC 1981 IPv6 Path MTU Discovery
	RFC 2460 IPv6 Specification
	RFC 2465 Management Information Base for IP Version
	6: Textual Conventions and General Group (partially support, only "IPv6 Interface Statistics table")
	RFC 3484 Default Address Selection for IPv6
	RFC 3513 IPv6 Addressing Architecture
	RFC 3587 IPv6 Global Unicast Address Format
	RFC 4007 IPv6 Scoped Address Architecture
	RFC 4862 IPv6 Stateless Address Auto-configuration

Security
RFC 1321 The MD5 Message-Digest Algorithm
RFC 1334 PPP Authentication Protocols (PAP)
RFC 1994 PPP Challenge Handshake Authentication Protocol (CHAP)

VPN continued
RFC 2405 The ESP DES-CBC Cipher Algorithm With Explicit IV
RFC 2406 IP Encapsulating Security Payload (ESP)
RFC 2410 The NULL Encryption Algorithm and Its Use With IPsec
RFC 2411 IP Security Document Roadmap
RFC 2451 The ESP CBC-Mode Cipher Algorithms
RFC 2473 Generic Packet Tunneling in IPv6 Specification
RFC 2529 Transmission of IPv6 over IPv4 Domains without Explicit Tunnels
RFC 2661 Layer Two Tunneling Protocol "L2TP"
RFC 2784 Generic Routing Encapsulation (GRE)
RFC 2868 RADIUS Attributes for Tunnel Protocol Support
RFC 2893 Transition Mechanisms for IPv6 Hosts and Routers
RFC 3602 The AES-CBC Cipher Algorithm and Its Use with IPsec
RFC 4214 Intra-Site Automatic Tunnel Addressing

Technical Specifications

RFC 2104 Keyed-Hashing for Message Authentication
 RFC 2138 RADIUS Authentication
 RFC 2618 RADIUS Authentication Client MIB
 RFC 2620 RADIUS Accounting Client MIB
 RFC 2716 PPP EAP TLS Authentication Protocol
 RFC 2865 RADIUS Authentication
 RFC 2866 RADIUS Accounting
 RFC 2867 RADIUS Accounting Modifications for Tunnel Protocol Support
 RFC 2868 RADIUS Attributes for Tunnel Protocol Support
 RFC 2869 RADIUS Extensions
 draft-grant-tacacs-02 (TACACS)

VPN

RFC 1701 Generic Routing Encapsulation (GRE)
 RFC 1702 Generic Routing Encapsulation over IPv4 networks.
 RFC 1828 IP Authentication using Keyed MD5
 RFC 1829 The ESP DES-CBC Transform
 RFC 1853 IP in IP Tunneling
 RFC 2085 HMAC-MD5 IP Authentication with Replay Prevention
 RFC 2401 Security Architecture for the Internet Protocol
 RFC 2402 IP Authentication Header
 RFC 2403 The Use of HMAC-MD5-96 within ESP and AH
 RFC 2404 The Use of HMAC-SHA-1-96 within ESP and AH

Protocol (ISATAP)

IKEv1

RFC 2407 The Internet IP Security Domain of Interpretation for ISAKMP
 RFC 2408 Internet Security Association and Key Management Protocol (ISAKMP).
 RFC 2409 The Internet Key Exchange (IKE)
 RFC 2412 The OAKLEY Key Determination Protocol
 RFC 3526 More Modular Exponential (MODP) Diffie-Hellman groups for Internet Key Exchange (IKE)
 RFC 3706 A Traffic-Based Method of Detecting Dead Internet Key Exchange (IKE) Peers

PKI

RFC 2510 Internet X.509 Public Key Infrastructure Certificate Management Protocols
 RFC 2511 Internet X.509 Certificate Request Message Format
 RFC 3279 Algorithms and Identifiers for the Internet X.509 Public Key Infrastructure Certificate and Certificate Revocation List (CRL) Profile
 RFC 3280 Internet X.509 Public Key Infrastructure Certificate and Certificate Revocation List (CRL) Profile
 draft-nourse-scep-06:
 PKCS#1
 PKCS#10
 PKCS#12
 PKCS#7

Features

Operating mode

Routing mode
 Transparent mode
 Hybrid mode

AAA services

RADIUS authentication
 HWTACACS authentication
 PKI/CA (x.509 format) authentication
 Domain authentication
 CHAP authentication
 PAP authentication

Firewall

Virtual firewall
 Security zone configuration
 Basic and extended ACLs
 Interface-based access control
 Time range-based access control

L2TP VPN

LNS, LAC
 L2TP Multi-instance

GRE VPN

IPSec/IKE

AH/ESP protocols
 Manual SA setup or through IKE
 ESP supports encryption algorithms of DES, 3DES, AES
 Algorithms of MD5 and SHA-1
 IKE main mode and aggressive mode
 NAT traversal
 DPD detection

IP services

IPv4/v6
 ARP

Technical Specifications

Dynamic packet filtering
ASPF packet filtering
Static and dynamic blacklists
MAC-IP binding
MAC-based access control
Transportation of 802.1Q-tagged packets

Anti virus

Virus definition-based detection
Library upgrading manually and automatically
Flow handing mode
Supporting protocols of HTTP, FTP, SMTP, and POP3.
Preventing virus types of Backdoor, Email-Worm, IM-Worm, P2P-Worm, Trojan, AdWare, Virus
Supporting virus logs and reports

URL filtering

Custom-defined URL filtering library
Supporting Java Blocking and ActiveX Blocking

Mail filtering

Blacklist of IP addresses
Matching keywords of the mail address, attachment
name, content, sender, and receiver

Security logs and statistics

User behavior flow logs
NAT translation logs
Real time logs of attacks
Blacklist logs
Address binding log
Traffic alarm logs
Traffic statistics and analysis
Global/security zone-based connection rate monitoring
Global/security zone-based protocol packet rate monitoring
Events statistics
E-mail notification of real-time alarms
Information distribution through E-mail

NAT

NAPT
PAT
NAT Server
Port mapping
Bidirectional NAT
Static NAT

Domain name resolution
IP unnumbered
DHCP relay
DHCP server
DHCP client

IP routing

Static routing
RIP v1/2
OSPF
BGP (only for U200-A)
Policy routing

High reliability (only for U200-A)

Active/Active mode
Active/Passive mode
Session Synchronization for Firewall

Attack prevention

DDoS
DNS query/SYN/ICMP/UDP/ARP flood
SYN cookie proxy SQL injection filtering
IP/MAC binding
IP spoofing detection
ARP reverse query checking
Management interfaces disabled by default

System and administration

Web interface via HTTP/HTTPS
Command line interface via console, telnet, SSH
RADIUS/TACACS+ server and local database authentication
DNS support for dynamic IP allocation
SNMP v1, 2c and 3

IPv6 Routing & Multicast

RIPng
OSPFv3
BGP4+ (only for U200-A)
Static Route
policy Route
PIM-SM/DM

IPv6 Security

NAT-PT
Manual tunnel
IPV6 OVER IPv4 GRE tunnel
6to4 tunnel (RFC3056)
ISATAP Tunnel
IPv6 Packet Filter
Radius
NAT64

Accessories

Memory	HP X600 1G Compact Flash Card	JC684A
	HP X600 512M Compact Flash Card	JC685A
	HP X600 256M Compact Flash Card	JC686A
HP U200-S UTM Appliance (JD273A)	HP U200-S 2-port Gig-T Module	JD265A
	HP U200-S 1-year Anti-Virus Service License	JG076A
	HP U200-S 1-year Anti-Spam Service LTU	JG075A
	U200-S 1-year URL Filter Service LTU	JG078A
HP U200-A UTM Appliance (JD275A)	HP U200-A 2-port Gig-T Module	JD266A
	HP U200-A 4-port GbE SFP Module	JD267A
	HP U200-A 1-year Anti-Spam Service License	JG064A
	HP U200-A 1-year Anti-Virus Service LTU	JG065A
	HP U200-A 1-year URL Filter Service LTU	JG067A

Summary of Changes

Date	Version History	Action	Description of Change
24-Jul-2014	From Version 4 to 6	Changed	This QuickSpecs was retired; no further updates will be made.
25-Jul-2012	From Version 3 to 4	Changed	Updated the Specifications sections of each model.
14-Jun-2012	From Version 2 to 3	Changed	Updated the Specifications section.
26-Mar-2012	From Version 1 to 2	Changed	Updated the Accessories and Features and Benefits sections.

To learn more, visit: <http://www.hp.com/networking>

© Copyright 2015 Hewlett-Packard Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.