

## Overview

## HP U200 Unified Threat Management (UTM) Appliance Series (Retired)

## Models

HP U200-S UTM Appliance

JD273A

HP U200-A UTM Appliance

JD275A

## Key features

- Flexible security zone and virtual firewall
- Advanced VPN
- Comprehensive threat protection
- Antivirus, antispam, and URL filtering options
- Intelligent Web-based management

## Product overview

The HP U200 Unified Threat Management (UTM) Appliance Series comprises a group of purpose-built security devices designed to provide comprehensive protection for distributed environments such as branch offices and remote sites. Utilizing a state-of-the-art multicore platform and advanced hardware acceleration, the U200 UTM appliance series delivers robust protection against malicious attacks that could compromise networks and their critical assets. Sharing the same proven technology as the HP VPN Firewall Module Family, the U200 UTM appliance series provides protection against known threats such as malware and denial-of-service (DoS) attacks while providing optional services such as antivirus, antispam, and URL filtering capabilities. This provides manageable, flexible security options for organizations and their unique deployment needs.

## Features and benefits

## Application highlights

- **Enhanced firewall functions:** provide basic functions such as security zone configuration, static/dynamic blacklist, MAC-IP binding, and ACL application; offer enhanced functions like status-based filtering, virtual firewall, and transportation of IEEE 802.1Q-tagged packets; protect the network against attacks from ARP spoofing, invalid TCP flag, large ICMP packets, Challenge Collapsar (CC), SYN flooding, and address/port scanning
- **Abundant VPN features:** HP U200 UTM appliances support access through L2TP VPN, GRE VPN, and IPSec VPN and SSL VPN; the integrated hardware encryption engine implements VPN handling of high performance
- **Zone-based access policies:** logically groups virtual LANs (VLANs) into zones that share common security policies; allows both unicast and multicast policy settings by zones instead of by individual VLANs
- **Application-level gateway (ALG):** deep packet inspection in the firewall discovers the IP address and service port information embedded in the application data; the firewall then dynamically opens appropriate connections for specific applications
- **Full support of NAT applications:** HP U200 UTM appliances support NAT applications, including many-to-one, many-to-many, static NAT, dual translation, easy IP, and DNS mapping; support NAT traversal with multiple protocols, and deliver NAT ALG functions such as DNS, FTP, H.323, and NBT
- **Real-time antivirus:** HP U200 UTM appliances adopt Kaspersky's antivirus engine to detect and remove codes of malicious attacks in a timely manner
- **Real-time spam filtering:** HP U200 UTM appliances filter spam in real time, which purifies mail systems
- **URL filtering:** HP U200 UTM appliances implement user-based URL access control to deny access to unauthorized websites
- **Enterprise-class high availability:** dual-box failover protects against loss of connectivity due to hardware failure, with automatic configuration and state table synchronization to simplify administration and remove scope for security policy inconsistencies

## Management

- **Complete session logging:** provides detailed information for problem identification and resolution

# QuickSpecs

## Overview

- **Manager and operator privilege levels:** enable read-only (operator) and read/write (manager) access on CLI and Web browser management interfaces
- **Secure Web GUI:** provides a secure, easy-to-use graphical interface for configuring the module via HTTPS
- **Command-line interface (CLI):** provides a secure, easy-to-use command-line interface for configuring the module via SSH or a switch console; provides direct real-time session visibility
- **SNMPv1, v2c, and v3:** facilitate centralized discovery, monitoring, and secure management of networking devices
- **Remote monitoring (RMON):** uses standard SNMP to monitor essential network functions; supports events, alarm, history, and statistics group plus a private alarm extension group
- **FTP, TFTP, and SFTP support:** FTP allows bidirectional transfers over a TCP/IP network and is used for configuration updates; Trivial FTP is a simpler method using User Datagram Protocol (UDP)

## Warranty and support

- **1-year warranty:** with advance replacement and 30-calendar-day delivery (available in most countries)
- **Electronic and telephone support:** limited electronic and telephone support is available from HP; to reach our support centers, refer to <http://www.hp.com/networking/contact-support>; for details on the duration of support provided with your product purchase, refer to <http://www.hp.com/networking/warrantysummary>
- **Software releases:** to find software for your product, refer to <http://www.hp.com/networking/support>; for details on the software releases available with your product purchase, refer to <http://www.hp.com/networking/warrantysummary>

## Technical Specifications

**HP U200-S UTM Appliance (JD273A)**

<b>Ports</b>	1 RJ-45 serial console port 5 auto-negotiating 10/100/1000 ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T) 1 Compact Flash port 1 module slot	
<b>Physical characteristics</b>	<b>Dimensions</b>	11.81(w) x 10.59(d) x 1.72(h) in (30 x 26.9 x 4.36 cm) (1U height)
	<b>Weight</b>	5.51 lb (2.5 kg)
<b>Memory and processor</b>	512 MB DDR2 SDRAM	
<b>Performance</b>	<b>MAC address table size</b>	4000 entries
<b>Environment</b>	<b>Operating temperature</b>	32°F to 113°F (0°C to 45°C)
	<b>Operating relative humidity</b>	10% to 95%, noncondensing
<b>Electrical characteristics</b>	<b>Voltage</b>	100-240 VAC
	<b>Current</b>	1.5 A
	<b>Maximum power rating</b>	54 W
	<b>Frequency</b>	50 / 60 Hz
	<b>Notes</b>	Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.
<b>Safety</b>	IEC 60950-1, Second Edition; UL60950-1, First Edition; EN60950-1, First Edition	
<b>Emissions</b>	VCCI Class B; EN 55022 Class B; ICES-003 Class B; FCC Part 15, Class B; EN 61000-3-2; EN 61000-3-3	
<b>Management</b>	IMC - Intelligent Management Center; command-line interface; Web browser; SNMP Manager; Telnet; HTTPS; FTP; Support HP A-IMC UTM Manager Software as unified management platform	
<b>Notes</b>	Performance <ul style="list-style-type: none"> <li>• 200 Mbps firewall throughput</li> <li>• 60,000 concurrent connections under firewall mode/16,000 concurrent connections under UTM mode</li> <li>• 6,000 new connections per second under firewall mode/2,000 new connections per second under UTM mode</li> <li>• 1,000 security policies</li> <li>• 100 Mbps 3DES/AES VPN throughput</li> <li>• 100 IPSec tunnels</li> <li>• 30 Mbps antivirus throughput</li> </ul>	
<b>Services</b>	Refer to the HP website at: <a href="http://www.hp.com/networking/services">http://www.hp.com/networking/services</a> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.	

**HP U200-A UTM Appliance (JD275A)**

<b>Ports</b>	RJ-45 serial console port 6 auto-negotiating 10/100/1000 ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T) 1 Compact Flash port 2 module slots	
<b>Physical characteristics</b>	<b>Dimensions</b>	17.4(w) x 16.06(d) x 1.74(h) in (44.2 x 40.8 x 4.42 cm) (1U height)
	<b>Weight</b>	8.82 lb (4 kg)
<b>Memory and processor</b>	1 GB DDR2 SDRAM	

## QuickSpecs

### Technical Specifications

<b>Performance</b>	<b>MAC address table size</b>	4000 entries
<b>Environment</b>	<b>Operating temperature</b>	32°F to 113°F (0°C to 45°C)
	<b>Operating relative humidity</b>	10% to 95%, noncondensing
<b>Electrical characteristics</b>	<b>Voltage</b>	100-240 VAC
	<b>Current</b>	2.5 A
	<b>Maximum power rating</b>	100 W
	<b>Frequency</b>	50 / 60 Hz
	<b>Notes</b>	Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.
<b>Safety</b>	IEC 60950-1, Second Edition; UL60950-1, First Edition; EN60950-1, First Edition	
<b>Emissions Management</b>	VCCI Class B; EN 55022 Class B; ICES-003 Class B; FCC Part 15, Class B; EN 61000-3-2; EN 61000-3-3	
<b>Management</b>	IMC - Intelligent Management Center; command-line interface; Web browser; SNMP Manager; Telnet; HTTPS; FTP; Support HP A-IMC UTM Manager Software as unified management platform	
<b>Notes</b>	<p>Performance</p> <ul style="list-style-type: none"> <li>• 800 Mbps firewall throughput</li> <li>• 500,000 concurrent connections under firewall mode/100,000 concurrent connections under UTM mode</li> <li>• 10,000 new connections per second under firewall mode/5,000 new connections per second under UTM mode</li> <li>• 10,000 security policies</li> <li>• 400 Mbps 3DES/AES VPN throughput</li> <li>• 1000 IPsec tunnels</li> <li>• 100 Mbps antivirus throughput</li> </ul>	
<b>Services</b>	Refer to the HP website at <a href="http://www.hp.com/networking/services">http://www.hp.com/networking/services</a> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.	

<b>Standards and protocols (applies to all products in series)</b>	<b>IPv6</b>
	RFC 1981 IPv6 Path MTU Discovery
	RFC 2460 IPv6 Specification
	RFC 2465 Management Information Base for IP Version
	6: Textual Conventions and General Group (partially support, only "IPv6 Interface Statistics table")
	RFC 3484 Default Address Selection for IPv6
	RFC 3513 IPv6 Addressing Architecture
	RFC 3587 IPv6 Global Unicast Address Format
	RFC 4007 IPv6 Scoped Address Architecture
	RFC 4862 IPv6 Stateless Address Auto-configuration
	<b>Security</b>
	RFC 1321 The MD5 Message-Digest Algorithm
	RFC 1334 PPP Authentication Protocols (PAP)
RFC 1994 PPP Challenge Handshake Authentication Protocol (CHAP)	

<b>VPN continued</b>
RFC 2405 The ESP DES-CBC Cipher Algorithm With Explicit IV
RFC 2406 IP Encapsulating Security Payload (ESP)
RFC 2410 The NULL Encryption Algorithm and Its Use With IPsec
RFC 2411 IP Security Document Roadmap
RFC 2451 The ESP CBC-Mode Cipher Algorithms
RFC 2473 Generic Packet Tunneling in IPv6 Specification
RFC 2529 Transmission of IPv6 over IPv4 Domains without Explicit Tunnels
RFC 2661 Layer Two Tunneling Protocol "L2TP"
RFC 2784 Generic Routing Encapsulation (GRE)
RFC 2868 RADIUS Attributes for Tunnel Protocol Support
RFC 2893 Transition Mechanisms for IPv6 Hosts and Routers
RFC 3602 The AES-CBC Cipher Algorithm and Its Use with IPsec
RFC 4214 Intra-Site Automatic Tunnel Addressing

## Technical Specifications

RFC 2104 Keyed-Hashing for Message Authentication

RFC 2138 RADIUS Authentication

RFC 2618 RADIUS Authentication Client MIB

RFC 2620 RADIUS Accounting Client MIB

RFC 2716 PPP EAP TLS Authentication Protocol

RFC 2865 RADIUS Authentication

RFC 2866 RADIUS Accounting

RFC 2867 RADIUS Accounting Modifications for Tunnel

Protocol Support

RFC 2868 RADIUS Attributes for Tunnel Protocol Support

RFC 2869 RADIUS Extensions

draft-grant-tacacs-02 (TACACS)

**VPN**

RFC 1701 Generic Routing Encapsulation (GRE)

RFC 1702 Generic Routing Encapsulation over IPv4 networks.

RFC 1828 IP Authentication using Keyed MD5

RFC 1829 The ESP DES-CBC Transform

RFC 1853 IP in IP Tunneling

RFC 2085 HMAC-MD5 IP Authentication with Replay Prevention

RFC 2401 Security Architecture for the Internet Protocol

RFC 2402 IP Authentication Header

RFC 2403 The Use of HMAC-MD5-96 within ESP and AH

RFC 2404 The Use of HMAC-SHA-1-96 within ESP and AH

Protocol (ISATAP)

**IKEv1**

RFC 2407 The Internet IP Security Domain of Interpretation for ISAKMP

RFC 2408 Internet Security Association and Key Management Protocol (ISAKMP).

RFC 2409 The Internet Key Exchange (IKE)

RFC 2412 The OAKLEY Key Determination Protocol

RFC 3526 More Modular Exponential (MODP)

Diffie-Hellman groups for Internet Key Exchange (IKE)

RFC 3706 A Traffic-Based Method of Detecting Dead

Internet Key Exchange (IKE) Peers

**PKI**

RFC 2510 Internet X.509 Public Key Infrastructure Certificate Management Protocols

RFC 2511 Internet X.509 Certificate Request Message

Format

RFC 3279 Algorithms and Identifiers for the Internet

X.509 Public Key Infrastructure Certificate and Certificate Revocation List (CRL) Profile

RFC 3280 Internet X.509 Public Key Infrastructure Certificate and Certificate Revocation List (CRL)

Profile

draft-nourse-scep-06:

PKCS#1

PKCS#10

PKCS#12

PKCS#7

**Features****Operating mode**

Routing mode

Transparent mode

Hybrid mode

**AAA services**

RADIUS authentication

HWTACACS authentication

PKI/CA (x.509 format) authentication

Domain authentication

CHAP authentication

PAP authentication

**Firewall**

Virtual firewall

Security zone configuration

Basic and extended ACLs

Interface-based access control

Time range-based access control

**L2TP VPN**

LNS, LAC

L2TP Multi-instance

**GRE VPN****IPSec/IKE**

AH/ESP protocols

Manual SA setup or through IKE

ESP supports encryption algorithms of DES, 3DES, AES

Algorithms of MD5 and SHA-1

IKE main mode and aggressive mode

NAT traversal

DPD detection

**IP services**

IPv4/v6

ARP

## Technical Specifications

Dynamic packet filtering  
 ASPF packet filtering  
 Static and dynamic blacklists  
 MAC-IP binding  
 MAC-based access control  
 Transportation of 802.1Q-tagged packets

**Anti virus**

Virus definition-based detection  
 Library upgrading manually and automatically  
 Flow handing mode  
 Supporting protocols of HTTP, FTP, SMTP, and POP3.  
 Preventing virus types of Backdoor, Email-Worm, IM-Worm, P2P-Worm, Trojan, AdWare, Virus  
 Supporting virus logs and reports

**URL filtering**

Custom-defined URL filtering library  
 Supporting Java Blocking and ActiveX Blocking

**Mail filtering**

Blacklist of IP addresses  
 Matching keywords of the mail address, attachment  
 name, content, sender, and receiver

**Security logs and statistics**

User behavior flow logs  
 NAT translation logs  
 Real time logs of attacks  
 Blacklist logs  
 Address binding log  
 Traffic alarm logs  
 Traffic statistics and analysis  
 Global/security zone-based connection rate monitoring  
 Global/security zone-based protocol packet rate monitoring  
 Events statistics  
 E-mail notification of real-time alarms  
 Information distribution through E-mail

**NAT**

NAPT  
 PAT  
 NAT Server  
 Port mapping  
 Bidirectional NAT  
 Static NAT

Domain name resolution  
 IP unnumbered  
 DHCP relay  
 DHCP server  
 DHCP client

**IP routing**

Static routing  
 RIP v1/2  
 OSPF  
 BGP (only for U200-A)  
 Policy routing

**High reliability (only for U200-A)**

Active/Active mode  
 Active/Passive mode  
 Session Synchronization for Firewall

**Attack prevention**

DDoS  
 DNS query/SYN/ICMP/UDP/ARP flood  
 SYN cookie proxy SQL injection filtering  
 IP/MAC binding  
 IP spoofing detection  
 ARP reverse query checking  
 Management interfaces disabled by default

**System and administration**

Web interface via HTTP/HTTPS  
 Command line interface via console, telnet, SSH  
 RADIUS/TACACS+ server and local database authentication  
 DNS support for dynamic IP allocation  
 SNMP v1, 2c and 3

**IPv6 Routing & Multicast**

RIPng  
 OSPFv3  
 BGP4+ (only for U200-A)  
 Static Route  
 policy Route  
 PIM-SM/DM

**IPv6 Security**

NAT-PT  
 Manual tunnel  
 IPV6 OVER IPv4 GRE tunnel  
 6to4 tunnel (RFC3056)  
 ISATAP Tunnel  
 IPv6 Packet Filter  
 Radius  
 NAT64

# QuickSpecs

## HP U200 Unified Threat Management (UTM) Appliance Series

### Accessories

<b>Memory</b>	HP X600 1G Compact Flash Card	JC684A
	HP X600 512M Compact Flash Card	JC685A
	HP X600 256M Compact Flash Card	JC686A
<b>HP U200-S UTM Appliance (JD273A)</b>	HP U200-S 2-port Gig-T Module	JD265A
	HP U200-S 1-year Anti-Virus Service License	JG076A
	HP U200-S 1-year Anti-Spam Service LTU	JG075A
	U200-S 1-year URL Filter Service LTU	JG078A
<b>HP U200-A UTM Appliance (JD275A)</b>	HP U200-A 2-port Gig-T Module	JD266A
	HP U200-A 4-port GbE SFP Module	JD267A
	HP U200-A 1-year Anti-Spam Service License	JG064A
	HP U200-A 1-year Anti-Virus Service LTU	JG065A
	HP U200-A 1-year URL Filter Service LTU	JG067A

# QuickSpecs

## HP U200 Unified Threat Management (UTM) Appliance Series

### Summary of Changes

<b>Date</b>	<b>Version History</b>	<b>Action</b>	<b>Description of Change</b>
24-Jul-2014	From Version 4 to 6	Changed	This QuickSpecs was retired; no further updates will be made.
25-Jul-2012	From Version 3 to 4	Changed	Updated the Specifications sections of each model.
14-Jun-2012	From Version 2 to 3	Changed	Updated the Specifications section.
26-Mar-2012	From Version 1 to 2	Changed	Updated the Accessories and Features and Benefits sections.

To learn more, visit: <http://www.hp.com/networking>

© Copyright 2015 Hewlett-Packard Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.