

QuickSpecs

Overview

HPE 527 802.11ac Dual Radio Unified Walljack Access Device Series

Models

HP 527 Dual Radio 802.11ac (AM) Unified Wired-WLAN Walljack	JH048A
HP 527 Dual Radio 802.11ac (WW) Unified Wired-WLAN Walljack	JH049A
HP 527 Dual Radio 802.11ac (JP) Unified Wired-WLAN Walljack	JH050A
HP 527 Dual Radio 802.11ac (IL) Unified Wired-WLAN Walljack	JH051A
HP 527 Dual Radio 802.11ac (AM) 20-unit Eco-pack Unified Wired-WLAN Walljack	JH052A
HP 527 Dual Radio 802.11ac (WW) 20-unit Eco-pack Unified Wired-WLAN Walljack	JH053A

Key features

- 802.11ac Dual Radio Walljack with one Gigabit Ethernet (GbE) uplink and three GbE access ports
- Four high-gain embedded antennas providing extended coverage and high-speed connectivity
- A single GbE Power over Ethernet (PoE) cable drop, reducing cabling, switch ports and local power
- Passthrough port as well as PoE out, reducing additional power needs to IP-based VoIP phone
- Limited Lifetime Warranty

Product overview

The HPE 527 802.11ac Unified Walljack is a dual radio 2.4GHz and 5GHz unified wired-wireless access point and GbE switch that works in sync with HPE Unified controllers, delivers high-performance networking solutions. The controllers provide advanced radio resource management (RRM).

This 527 802.11ac Unified Walljack provides one GbE uplink port, three GbE ports, one 802.11b/g/n radio, one 802.11ac radio, and a pass-through RJ-45 connection to support a range of service and user connectivity options. One of the front panel GbE ports can be configured as an IEEE 802.3af-compliant PoE forwarding port to enable devices such as IP telephones to be powered directly from the Walljack.

The HPE 527 802.11ac Dual Radio Unified Walljack uses a single PoE cable drop, reducing cabling, switch ports, and power sourcing equipment. The HPE 527 provides unified wired-wireless connectivity into a low-profile design that can be quickly, easily and discretely installed in a standard wall outlet box. The HPE 527 is designed to provide wireless coverage for one or more rooms.

Features and benefits

Management

- **Hewlett Packard Enterprise Wi-Fi Clear Connect**
 - provides a system-wide approach to improving WLAN reliability by proactively determining and adjusting to changing RF conditions; helps optimize WLAN performance by detecting interference from Wi-Fi and non-Wi-Fi sources using spectrum analysis capabilities built into the Walljack, identifying rogue activity, and making decisions at a system-wide level
- **Advanced radio resource management**
 - **Automatic radio power adjustments**
 - include real-time power adjustments based on changing environmental conditions and signal coverage adjustment

Overview

- **Automatic radio channel**
provides intelligent channel switching and real-time Interference detection
- **Intelligent client load balancing**
determines number of clients across neighboring APs and adjusts client allocation to balance the load
- **Airtime fairness**
provides equal RF transmission time for wireless clients
- **Spectrum Analysis**
 - **Power/frequency spectrum analysis**
measures noise from IEEE 802.11 remote sources
 - **Signal detection/classification**
identifies source of RF interference, for example, Bluetooth, cordless phones, and microwave ovens
 - **Evaluation of channel quality**
helps detect severe channel degradation and improve the reporting of poor RF performance
- **Integrated wireless IDS/IPS**
detects and locates and mitigates unknown and rogue devices (see controller datasheet for details)
- **HPE Intelligent Management Center and Wireless Services Manager**
provides central management for discovery, logging, status, and configuration management
- **Enhanced AP survivability**
continues to operate using the existing configuration while the AP searches for a new controller
- **Compatible with HPE Unified Controllers**
Refer to the HPE Access Point—Controller Compatibility Matrix at <http://h20195.www2.hp.com/V2/GetDocument.aspx?docname=4AA5-0345ENW&cc=us&lc=en>

Quality of Service (QoS)

- **Rate limiting**
 - supports per-wireless client ingress-enforced maximums and per-wireless client, per-queue guaranteed minimums
- **Centralized traffic**
 - maintains Layer 2 and Layer 3 QoS settings when using centralized traffic or guest access
- **IEEE 802.1p prioritization**
delivers data to devices based on the priority and type of traffic
- **Wireless**
 - **L2/L3/L4 classification**
IEEE 802.1p VLAN priority and DiffServ
 - **Multiple SSIDs per radio**
Wi-Fi MultiMedia (WMM), IEEE 802.11e EDCF, and Service-Aware priority

Connectivity

- **IEEE 802.3af Power over Ethernet support**
simplifies deployment and dramatically reduces installation costs by helping to eliminate the time and cost involved in supplying local power at each access point location. Unit can be powered by IEEE 802.3af or IEEE 802.3at (PoE+) source
- **Power Forwarding**
PoE Class 1/2/3 when powered via IEEE 802.3at (PoE+)
- **Auto-MDIX**
automatically adjusts for straight-through or crossover cables on all Ethernet interfaces

Mobility

Overview

- **Two spatial stream MIMO technology**
 - **2x2:2 MIMO**
provides 802.11b/g/n and 802.11ac Wi-Fi technology, which allows for 866 Mbps of signaling @ 5GHz and 300 Mbps for 802.11n
 - **Embedded antenna**
provides excellent coverage through use of two 2 dBi embedded antennae; no need for the added cost of external antennas
- **Interoperability**
 - meets Wi-Fi Alliance Certifications, including IEEE 802.11b/g/n/ac to help ensure multivendor interoperability
- **Multiple SSIDs**
 - Up to 16 SSIDs per radio, each with unique MAC address, configurable SSID broadcasts
 - Individual security and QoS profiles
 - Configurable DTIM and minimum data rate
 - Each mapped to separate IEEE 802.1Q VLANs
 - WMM and/or WMM-PS
 - Security filter
 - IP filter
- **AP client access control functions**
 - offers IEEE 802.1X authentication using EAP-SIM, EAP-FAST, EAP-TLS, EAP-TTLS, and PEAP
 - delivers MAC address authentication using local or RADIUS access lists
 - provides RADIUS AAA using EAP-MD5, PAP, CHAP, and MS-CHAPv2
 - supports RADIUS Client (RFC 2865 and 2866) with location-aware support
 - provides Layer 2 wireless client isolation

Security

- **Choice of IEEE 802.11i, WPA2, or WPA**
locks out unauthorized wireless access by authenticating users prior to granting network access; robust Advanced Encryption Standard (AES) or Temporal Key Integrity Protocol (TKIP) encryption secures the data integrity of wireless traffic
- **IEEE 802.1X support**
provides port-based user authentication with support for Extensible Authentication Protocol (EAP) MD5, TLS, TTLS, and PEAP with choice of AES, TKIP, and static or dynamic WEP encryption for protecting wireless traffic between authenticated clients and the access point
- **Local wireless bridge client traffic filtering**
prevents communication between wireless devices associated with the same access point

Additional information

- **RFC Support**
refer to the controller datasheet for specific RFCs and other industry standards supported

Warranty and support

- **Limited Lifetime Warranty**
see <http://www.hpe.com/networking/warrantysummary> for warranty and support information included with your product purchase.
- **Software releases**
to find software for your product, refer to <http://www.hpe.com/networking/support>; for details on the software releases available with your product purchase, refer to <http://www.hpe.com/networking/warrantysummary>

Configuration

Build To Order: BTO is a standalone unit with no integration. BTO products ship standalone are not part of a CTO or Rack-Shippable solution.

HP 527 802.11ac (AM) Unified Walljack

JH048A

See Configuration **NOTE:1**

- 1 RJ-45 autosensing 10/100/1000 PoE uplink port
- 2 RJ-45 autosensing 10/100/1000 downward facing ports
- 1 RJ-45 autosensing 10/100/1000 downward facing PoE port
- 1 RJ-45 pass through port
- Wireless - 802.11b/g/n, a/n/ac

HP 527 802.11ac (WW) Unified Walljack

JH049A

See Configuration **NOTE:2**

- 1 RJ-45 autosensing 10/100/1000 PoE uplink port
- 2 RJ-45 autosensing 10/100/1000 downward facing ports
- 1 RJ-45 autosensing 10/100/1000 downward facing PoE port
- 1 RJ-45 pass through port
- Wireless - 802.11b/g/n, a/n/ac

HP 527 802.11ac (JP) Unified Walljack

JH050A

See Configuration **NOTE:4**

- 1 RJ-45 autosensing 10/100/1000 PoE uplink port
- 2 RJ-45 autosensing 10/100/1000 downward facing ports
- 1 RJ-45 autosensing 10/100/1000 downward facing PoE port
- 1 RJ-45 pass through port
- Wireless - 802.11b/g/n, a/n/ac

HP 527 802.11ac (IL) Unified Walljack

JH051A

See Configuration **NOTE:3**

- 1 RJ-45 autosensing 10/100/1000 PoE uplink port
- 2 RJ-45 autosensing 10/100/1000 downward facing ports
- 1 RJ-45 autosensing 10/100/1000 downward facing PoE port
- 1 RJ-45 pass through port
- Wireless - 802.11b/g/n, a/n/ac

HP 527 802.11ac (AM) 20Pk Unifd Walljack

JH052A

See Configuration **NOTE:1**

- 1 RJ-45 autosensing 10/100/1000 PoE uplink port
- 2 RJ-45 autosensing 10/100/1000 downward facing ports
- 1 RJ-45 autosensing 10/100/1000 downward facing PoE port
- 1 RJ-45 pass through port
- Wireless - 802.11b/g/n, a/n/ac

HP 527 802.11ac (WW) 20Pk Unifd Walljack

JH053A

See Configuration **NOTE:2**

- 1 RJ-45 autosensing 10/100/1000 PoE uplink port
- 2 RJ-45 autosensing 10/100/1000 downward facing ports
- 1 RJ-45 autosensing 10/100/1000 downward facing PoE port
- 1 RJ-45 pass through port
- Wireless - 802.11b/g/n, a/n/ac

Configuration Rules:

Configuration

- Note 1 Only available in AMS. (Warning in Clic only)
- Note 2 Not available in AMS, Japan or Israel. (Warning in Clic only)
- Note 3 Only available in Israel. (Warning in Clic only)
- Note 4 Only available in Japan. (Warning in Clic only)

527 Unified Walljack Options

External Power Supplies

HP Single-PRT 802.3at Gig PoE PS	J9867A See Configuration NOTE:1, 5
HP 1-port Power Injector	J9407B See Configuration NOTE:4, 5

Configuration Rules:

- Note 1 This power supply is supported on the following Walljacks:
- | | |
|--|--------|
| HP 527 Dual Radio 802.11ac (AM) Unified Wired-WLAN Walljack | JH048A |
| HP 527 Dual Radio 802.11ac (WW) Unified Wired-WLAN Walljack | JH049A |
| HP 527 Dual Radio 802.11ac (JP) Unified Wired-WLAN Walljack | JH050A |
| HP 527 Dual Radio 802.11ac (IL) Unified Wired-WLAN Walljack | JH051A |
| HP 527 Dual Radio 802.11ac (AM) 20-unit Eco-pack Unified Wired-WLAN Walljack | JH052A |
| HP 527 Dual Radio 802.11ac (WW) 20-unit Eco-pack Unified Wired-WLAN Walljack | JH053A |
- Note 4 Using this 1-port Power Injector will disable the PoE Output port on the HPE 527. It is recommended you use the J9867A - HPE Single-PRT 802.3at Gig PoE PS instead:
- | | |
|--|--------|
| HP 527 Dual Radio 802.11ac (AM) Unified Wired-WLAN Walljack | JH048A |
| HP 527 Dual Radio 802.11ac (WW) Unified Wired-WLAN Walljack | JH049A |
| HP 527 Dual Radio 802.11ac (JP) Unified Wired-WLAN Walljack | JH050A |
| HP 527 Dual Radio 802.11ac (IL) Unified Wired-WLAN Walljack | JH051A |
| HP 527 Dual Radio 802.11ac (AM) 20-unit Eco-pack Unified Wired-WLAN Walljack | JH052A |
| HP 527 Dual Radio 802.11ac (WW) 20-unit Eco-pack Unified Wired-WLAN Walljack | JH053A |
- Note 5 Localization required. (See Localization Menu)

Mounting Kit

HP Unified Walljack Table Mount Kit	JL022A See Configuration NOTE:1
-------------------------------------	---

Configuration

Configuration Rules:

Note 1	This Mounting Kit is supported on the following Walljacks:	
	HP 527 Dual Radio 802.11ac (AM) Unified Wired-WLAN Walljack	JH048A
	HP 527 Dual Radio 802.11ac (WW) Unified Wired-WLAN Walljack	JH049A
	HP 527 Dual Radio 802.11ac (JP) Unified Wired-WLAN Walljack	JH050A
	HP 527 Dual Radio 802.11ac (IL) Unified Wired-WLAN Walljack	JH051A
	HP 527 Dual Radio 802.11ac (AM) 20-unit Eco-pack Unified Wired-WLAN Walljack	JH052A
	HP 527 Dual Radio 802.11ac (WW) 20-unit Eco-pack Unified Wired-WLAN Walljack	JH053A

Technical Specifications

HP 527 Dual Radio 802.11ac (AM) Unified Wired-WLAN Walljack (JH048A)

HP 527 Dual Radio 802.11ac (WW) Unified Wired-WLAN Walljack (JH049A)

HP 527 Dual Radio 802.11ac (JP) Unified Wired-WLAN Walljack (JH050A)

HP 527 Dual Radio 802.11ac (IL) Unified Wired-WLAN Walljack (JH051A)

HP 527 Dual Radio 802.11ac (AM) 20-unit Eco-pack Unified Wired-WLAN Walljack (JH052A)

HP 527 Dual Radio 802.11ac (WW) 20-unit Eco-pack Unified Wired-WLAN Walljack (JH053A)

I/O ports and slots	2 RJ-45 autosensing 10/100/1000 ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T); Duplex: 10BASE-T/100BASE-TX: half or full; 1000BASE-T: full only	
	1 RJ-45 autosensing 10/100/1000 PoE port (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T, IEEE 802.3af PoE); Duplex: 10BASE-T/100BASE-TX: half or full; 1000BASE-T: full only	
	1 RJ-45 autosensing 10/100/1000 PoE+ port (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T, IEEE 802.3at PoE+); Duplex: 10BASE-T/100BASE-TX: half or full; 1000BASE-T: full only	
	1 RJ-45 pass through port	
Additional ports and slots	1 USB 2.0	
AP characteristics	Radios (built-in)	802.11a/b/g/n/ac
	Radio operation modes	Client access, Packet capture
	AP operation modes	Controlled
	Wi-Fi Alliance Certification	a/b/g/n/ac Wi-Fi Certified
	Antenna	(2) 2 dBi 2.4 GHz and (2) 2 dBi 5 GHz omnidirectional antennas
	Number of internal antennas	4
Physical characteristics	Dimensions	3.4(w) x 5.91(d) x 1.38(h) in (8.6 x 15 x 3.5 cm)
	Weight	0.77 lb (0.35 kg) mounting bracket
Mounting and enclosure	Includes mounting bracket and screws for wall installation.	
Environment	Operating temperature	32°F to 113°F (0°C to 45°C)
	Operating relative humidity	5% to 95%, noncondensing
	Nonoperating/Storage temperature	-40°F to 158°F (-40°C to 70°C)
	Nonoperating/Storage relative humidity	5% to 95%, noncondensing
Electrical characteristics	Description	The HPE 527 Walljack, when powered through the uplink GbE PoE/PoE+ port, acts as a PoE PD complying with the IEEE 802.3af/at standards. The HPE 527 Walljack can also provide power to its USB 2.0 port (maximum 5V/0.5A output).
	Maximum power rating	12.9 W without supplying power and 25.5 W supplying 802.3af power out the customer facing port
	Notes	Optional 48 VDC power supply

Technical Specifications

Frequency band and Operating channels	<p>Americas</p> <p>2.412 - 2.462 GHz (1 - 11 channels) 5.180 - 5.320 GHz (36 - 64 channels) 5.500 - 5.700 GHz (100 - 140 (excluding 5600-5670 MHz) channels) 5.745 - 5.825 GHz (149 - 165 channels)</p> <p>European Union</p> <p>2.412 - 2.472 GHz (1 - 13 channels) 5.180 - 5.320 GHz (36 - 64 channels) 5.500 - 5.700 GHz (100 - 140 (excluding 5600-5650 MHz) channels)</p> <p>Rest of World (Actual channels designated by selecting country in UI)</p> <p>2.412 - 2.472 GHz (1 - 13 channels) 5.180 - 5.320 GHz (36 - 64 channels) 5.500 - 5.700 GHz (100 - 140 channels) 5.745 - 5.825 GHz (149 - 165 channels)</p> <p>Taiwan</p> <p>2.412 - 2.462 GHz (1 - 11 channels) 5.280 - 5.320 GHz (56 - 64 channels) 5.500 - 5.700 GHz (100 - 140 (excluding 5600-5670 MHz) channels) 5.745 - 5.825 GHz (149 - 165 channels)</p> <p>Japan</p> <p>2.412 - 2.472 GHz (1 - 13 channels) 5.180 - 5.320 GHz (36 - 64 channels) 5.500 - 5.700 GHz (100 - 140 channels)</p> <p>Israel</p> <p>2.412 - 2.472 GHz (1 - 13 channels) 5.180 - 5.320 GHz (36 - 64 channels)</p>
Radio	FCC Part 15.247; FCC Part 15.407 (US); RSS-210 (Canada); EN 300 328; ARIB STD-T66; IDA Registration (Singapore); RCR STD-33; ARIB STD-T71 (Japan); EN 301 893 (EU); KCC approval (Korea)
Safety	UL 2043; UL 60950-1; IEC 60950-1; EN 60950-1; CAN/CSA-C22.2 No. 60950-1
Medical	EN60601-1-2
RF Exposure	FCC Bulletin OET-65C; RSS-102; CFR 47, Part 2, Subpart J; ANSI/IEEE C95.1 (99); Ministry of Health Safety Code 6; Australian Radiation Protection Std.
Features	<p>Dual radio: IEEE 802.11a/n/ac for very high-throughput applications and IEEE 802.11b/g/n for legacy support applications</p> <ul style="list-style-type: none"> - Integrated antennas for both IEEE radios, supporting two spatial streams and 2x2 MIMO - Four embedded antennas - Both radios operate at full power and full performance on IEEE 802.3af PoE/Gigabit Ethernet
Emissions	EN 55022 Class B; EN 60601-1-2; EN 301 489-1; EN 301 489-17; ICES-003 Class B; FCC Part 15, Class B
Notes	<p>Supported data rates</p> <ul style="list-style-type: none"> • 802.11b: 1, 2, 5.5, 11 Mbps • 802.11a/g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps • 802.11n: 6.5 to 300 Mbps (MCS0 to MCS15, 1 and 2 spatial streams) • 802.11ac: 6.5 to 866 Mbps (MCS0 to MCS9, 1 and 2 spatial streams) • 802.11n high-throughput (HT) 20/40 • 802.11ac very high throughput (VHT) 20/40/80 • 802.11n/ac packet aggregation A-MPDU and A-MSDU <p>The HPE 527 Walljack power information listed includes the embedded antenna. Review the Hewlett Packard Enterprise documentation for your AP to understand the maximum output setting for your AP based on your country's regulations.</p> <p>Two spatial stream AP Walljack, supporting 866 Mbps in the 5GHz band and 300 Mbps in the 2.4GHz band.</p> <p>Maximum transmit power varies by country.</p> <p>Regulatory model number: BJNGA-FB0005</p>
Services	Refer to the Hewlett Packard Enterprise website at http://www.hpe.com/networking/services for

Technical Specifications

details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office.

Radio characteristics

- HP 527 Dual Radio 802.11ac (AM) Unified Wired-WLAN Walljack (JH048A)**
- HP 527 Dual Radio 802.11ac (WW) Unified Wired-WLAN Walljack (JH049A)**
- HP 527 Dual Radio 802.11ac (JP) Unified Wired-WLAN Walljack (JH050A)**
- HP 527 Dual Radio 802.11ac (IL) Unified Wired-WLAN Walljack (JH051A)**
- HP 527 Dual Radio 802.11ac (AM) 20-unit Eco-pack Unified Wired-WLAN Walljack (JH052A)**
- HP 527 Dual Radio 802.11ac (WW) 20-unit Eco-pack Unified Wired-WLAN Walljack (JH053A)**

NOTE: This transmit power data is EIRP and includes the embedded antennas. The receiver sensitivity also includes the antenna gain.

IEEE 802.11ac 5GHz @ 80MHz channel	Data rate	MCS9 - 866 Mbps	MCS0 - 65 Mbps
	Receiver sensitivity	-59 dBm	-85 dBm
	Transmit power	18 dBm	22 dBm
IEEE 802.11ac 5GHz @ 40MHz channel	Data rate	MCS9 - 400 Mbps	MCS0 - 30 Mbps
	Receiver sensitivity	-62 dBm	-88 dBm
	Transmit power	18 dBm	22 dBm
IEEE 802.11n 5GHz @ 40MHz channel	Data rate	MCS15 - 300 Mbps	MCS8 - 30 Mbps
	Receiver sensitivity	-69 dBm	-88 dBm
	Transmit power	19 dBm	22 dBm
IEEE 802.11n 5GHz @ 20MHz channel	Data rate	MCS15 - 144.4 Mbps	MCS8 - 14.4 Mbps
	Receiver sensitivity	-72 dBm	-92 dBm
	Transmit power	19 dBm	22 dBm
IEEE 802.11n 2.4GHz @ 40MHz channel	Data rate	MCS15 - 300 Mbps	MCS8 - 30 Mbps
	Receiver sensitivity	-69 dBm	-89 dBm
	Transmit power	20 dBm	22 dBm
IEEE 802.11n 2.4GHz @ 20MHz channel	Data rate	MCS15 - 144.4 Mbps	MCS8 - 14.4 Mbps
	Receiver sensitivity	-72 dBm	-93 dBm
	Transmit power	20 dBm	22 dBm
IEEE 802.11a 5GHz	Data rate	54 Mbps	6 Mbps

Technical Specifications

Receiver sensitivity	-75 dBm	-92 dBm
Transmit power	20 dBm	22 dBm

IEEE 802.11b/g 2.4GHz	Data rate	54 Mbps	11 Mbps	6 Mbps	1 Mbps
	Receiver sensitivity	-76 dBm	-89 dBm	-93 dBm	-96 dBm
	Transmit power	20 dBm	22 dBm	22 dBm	22 dBm

Standards and Protocols

(applies to all products in series)

Mobility

IEEE 802.11a High Speed Physical Layer in the 5 GHz Band
 IEEE 802.11ac WLAN Enhancements for Very High Throughput
 IEEE 802.11b Higher-Speed Physical Layer Extension in the 2.4 GHz Band
 IEEE 802.11d Global Harmonization
 IEEE 802.11g Further Higher Data Rate Extension in the 2.4 GHz Band
 IEEE 802.11h Dynamic Frequency Selection
 IEEE 802.11i Medium Access Control (MAC) Security Enhancements
 IEEE 802.11n Dual Band WLAN Enhancements for Higher Throughput

NOTE: All of the above standards are now included in IEEE 802.11-2012

Accessories**HPE 527 802.11ac Dual Radio Unified Walljack Access Device Series accessories****Power Supply**

HP 1-port Power Injector	J9407B
HP Single-Port 802.3at Gigabit PoE In-Line Power Supply	J9867A
HP Gigabit Intellijack 48V Power Supply	JD055B

Mounting Kit

HP Unified Wired-WLAN Walljack Table / Flush Wall Mount Kit	JL022A
---	--------

Summary of Changes

Date	Version History	Action	Description of Change
01-Dec-2015	From Version 1 to 2	Changed	Overview and Technical Specifications updated



Sign up for updates

★ Rate this document

© Copyright 2015 Hewlett Packard Enterprise Development LP. The information contained herein is subject to change without notice. The only warranties for Hewlett Packard Enterprise products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. Hewlett Packard Enterprise shall not be liable for technical or editorial errors or omissions contained herein.

To learn more, visit: <http://www.hp.com/networking>

c04519014 - 15155 - Worldwide - V2 - 1-December-2015

